

# EUROLIVE

# B215

## Technical Specifications

GB

Version 1.1 May 2006



[www.behringer.com](http://www.behringer.com)



## EUROLIVE B215

---

# EUROLIVE

### 600-Watt, 2-Way PA Speaker System with 15" Woofer and 1.75" Compression Driver

GB

- ▲ High-power 2-Way PA sound reinforcement speaker system for live and playback applications (150-Watt Continuous/600-Watt Peak Power)
- ▲ Ultra-compact and lightweight system delivers excellent sound even at extreme sound pressure levels
- ▲ Extremely powerful 15" long-excursion driver provides incredibly deep bass and acoustic power
- ▲ State-of-the-art 1.75" compression driver for exceptional high-frequency reproduction
- ▲ Ultra-wide dispersion, large-format exponential/conical horn
- ▲ Overload-protection circuitry ensures optimal HF driver protection
- ▲ Versatile trapezoidal enclosure design allows different positioning:
  - Stand mounting with 35-mm pole socket
  - Tilts on its side for use as a floor monitor
- ▲ Ergonomically shaped handles for easy carrying and setup
- ▲ 2 professional speaker connectors (compatible with Neutrik® Speakon®) plus ¼" jack connectors\*
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

---

\* All Trademarks mentioned belong to their respective owners and are not affiliated with BEHRINGER®

## SPECIFICATIONS

### SYSTEM DATA

High-performance woofer	15" (381 mm)
Tweeter compression driver	1.75" (44 mm)
Frequency range	55 Hz to 20 kHz
Power rating (Peak Program)	600 W
Impedance	8 $\Omega$
Sensitivity (1 W @ 1 m)	95 dB (Full Space)
Dispersion	70° x 40°
Crossover frequency	1.8 kHz

### DIMENSIONS/WEIGHT

Dimensions (H x W x D)	approx. 27 1/3" x 17 1/3" x 13 1/16" (695 mm x 440 mm x 335 mm)
Weight	approx. 39.7 lbs. (18.0 kg)

GB

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER nor affiliation of the trademark owners with BEHRINGER. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGER by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2006 BEHRINGER Spezielle Studiotechnik GmbH,  
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Muenchheide II, Germany.  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903