

EUROSTACK PRO RX1602



Technical Specifications

VERSION 1.4 December 2003

ENGLISH

www.behringer.com



EURORACK PRO RX1602

EURORACK PRO

PROFESSIONAL MULTI-PURPOSE 16-INPUT ULTRA-LOW NOISE LINE MIXER



- ▲ Extremely flexible keyboard and multi-purpose sub-mixer, multi-track monitoring mixer, level translator, FX return sub-mixer, etc.
- ▲ 16 balanced high-headroom line inputs for individual stereo or mono use of each section
- ▲ Ultra-low noise ULN design, highest possible headroom, ultra-transparent audio
- ▲ Dedicated balance and level controls plus +4/-10 level selection per channel
- ▲ Monitor/FX send control per section with global master send control for flexible monitoring, recording or effects applications
- ▲ Illuminated double-function “mute” button per section with additional “clip” indication provides comfortable input source/level information
- ▲ Monitor/FX signal assignable to phones output for added flexibility
- ▲ Highly accurate 2 x 7-segment LED level meters and individual level control for left and right main mix signal
- ▲ 1/4” TRS main mix outputs plus easily accessible headphones output on the front panel with dedicated level control
- ▲ High-quality detented rotary controls for long-term reliability
- ▲ Shielded toroidal power transformer for lowest noise interference
- ▲ High-quality component components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

SPECIFICATIONS

AUDIO INPUTS

INPUT L/R	
Type	1/4" TRS connector, electronically balanced
Impedance	approx. 20 k Ω balanced, 10 k Ω unbalanced
Gain range	$-\infty$ to +15 dB
Operating level	variable, +4 dBu/-10 dBV, switchable
Max. input level	+22 dBu
Common-mode rejection CMRR @ 1 kHz	typ. 44 dB

AUDIO OUTPUTS

MAIN OUT L/R	
Type	1/4" TRS connector, unbalanced
Gain range	$-\infty$ to +15 dB
Impedance	approx. 120 Ω
Max. output level	+22 dBu

MON OUT

Type	1/4" TRS connector, unbalanced, mono
Impedance	approx. 120 Ω
Max. output level	+22 dBu

PHONES output

Type	1/4" TRS connector, stereo
Minimum load impedance	100 Ω

SYSTEM SPECIFICATIONS

Bandwidth	20 Hz - 20 kHz +/-0.2 dB
Frequency range	20 Hz - 200 kHz +/-3 dB
Signal-to-noise ratio	< -97 dB
THD	0.0025% @ +4 dB input 1 kHz gain 1
Crosstalk	< -70 dB

POWER SUPPLY

Voltage	
USA/Canada	120 V~, 60 Hz
Europe/U.K./Australia	230 V~, 50 Hz
Japan	100 V~, 50 - 60 Hz
General export model	120/230 V~, 50 - 60 Hz
Power consumption	max. 14 W
Fuse	100 - 120 V~: T 630 mA H 200 - 240 V~: T 315 mA H
Mains connection	Standard IEC connector

DIMENSIONS/WEIGHT

Dimensions (H x W x D)	approx. 1 3/4" (44.5 mm) x 19" (482.6 mm) x 8 1/2" (217 mm)
Weight	approx. 2.30 kg (5.07 lbs)
Shipping weight	approx. 3.55 kg (7.83 lbs)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications depicted may vary slightly from product. No part of this book may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studioteknik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2003 BEHRINGER Spezielle Studioteknik GmbH.
BEHRINGER Spezielle Studioteknik GmbH, Hanns-Martin-Schleyer-Str. 36-38,
47877 Willich-Müncheide II, Germany
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903