

MORGAN SOUND 專業舞台喇叭



MG SX-100



MG F215



MG SX-300



MG W2P



MG SX-500

Specifications

型號	MG SX-100	MG SX-300	MG SX-500	MG F215	MG W2P
特性	兩音路	兩音路	兩音路	兩音路	兩音路
低音單體	10"	12"	15"	15"X2	12"
中音單體				3英寸	
高音單體	1"(號角)	1"(號角)	1"(號角)	2"(號角)	1"(號角)
頻率響應(±3db)	36~25k	45~20k	45~20k	45~17k	60HZ-18KHZ
平均功率	150w	300w	350w	800w	300w
最大功率	450w	1000w	1050w	1600w	1200w
靈敏度(1w/m±3db)	99db	101db	110db	102db	112db
最大音壓			103db SPL	130db SPL	128db
輸入阻抗	8Ω	8Ω	8Ω	4Ω	8Ω
放射角度	60° X130°	60° X130°	60° X130°	40° X130°	70° X40°
尺寸(cm)	50x41x30	57x42x34	68x45x35	125x45x59	55x37x34
重量	13kg	23kg	26kg	60kg	24kg
箱體型式	聚乙炔防水外殼				

M3

INPUTS	2xXLR3 20k ohms electronically, balanced CMRR 60dB 20Hz - 10kHz
OUTPUTS	4xXLR3 electronically balanced
MAX OUTPUT	+20dBu into 600ohms
FREQUENCY RESPONSE	-3dB@18Hz 12dB/octave -3dB@45Hz 12dB/octave (ultimately set by system parameters)
SYSTEM PARAMETERS	Crossover frequencies and slopes, level matching and phase adjustments defined by plug-in board
LIMITERS	Individual for each channel Ratio 20:1. Threshold range -12dBu to +12dBu in 16steps
DIMENSIONS	WIDTH 483mm(19ins) HEIGHT 44mm(1.75ins)1U DEPTH 155(6.1ins) WEIGHT 2.4kg(5.3lbs)

