






Features /

Compact two-way passive system ,
 Multi-angle birch ply enclosure ,
 User rotatable 90° x 50° horn ,
 High power output Flexible mounting options

Applications/

Club sound reinforcement ,
 Unobtrusive stage monitoring ,
 Fill-in system for main PA ,
 AV presentations



Technical Specifications

Rated Power AES	200W	300W	400W
Peak Power	800W	1200W	1200W
Nominal Impedance	8Ω	8Ω	8Ω
Frequency Response(+/-3dB)	65Hz--19KHz	65Hz--18KHz	55Hz--18KHz
Sensitivity(2.83V/1m)	96dB	97dB	99dB
Maximum Spl Continuous	119dB	120dB	123dB
Maximum Spl Peak	125dB	126dB	129dB
Dispersion -6dB			
Horizontal	90°	80°	90°
Vertical	50°	50°	50°
Drive Specification			
LF Drive	1X10"(255mm)/2.5"Voice Coil	1X12"[310mm]/3"Voice Coil	1X15"[390mm]/3"Voice Coil
HF Drive	1"exit Compression Driver 1.75"Voice Coil	1"exit Compression Driver 1.75"Voice Coil	1.4"exit Compression Driver 3"Voice Coil
Connectors	Low profile 20 amp push-lock	Low profile 20 amp push-lock	Low profile 20 amp push-lock
Enclosure Material	Plywood	Plywood	Plywood
Cabinet Finish	Textured Polyester Paint	Textured Polyester Paint	Textured Polyester Paint
Hoisting Set	12 x M8	12 x M8	14 x M8
Dimensions (WxDxD)	310X493X310	354X560X364	430X690X415
Weight(kg)	15kg	20kg	31.5kg